

Inners Only™, MACXLine® Rigid Line



Inners Only™ Inner Conductors Replacement System

The Inexpensive Alternative to Transmission Line Replacement

MACXLine® transmission lines are available as Inners Only™ replacements. Since MACXLine® lengths are identical to those of standard rigid line, it is an excellent choice for any application.

Conventional rigid transmission line systems require maintenance after just ten years to avoid premature burnout of bullet-style connectors. By upgrading with ERI Inners Only™ before your existing transmission line fails, you avoid the disaster of dead air.

MACXLine® Inners Only™ replacements provide the ultimate in operational dependability at about half the cost of a new installation. You swap your worn-out, failure-prone bullets and inner conductors for the most dependable components in the industry while reusing your expensive outer conductors, which are normally good for many more years of service.

Inners Only™

Type No.	Description
----------	-------------

MACX350A, 3-1/8" 50-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX350A-25-*	Variable length inner conductor
MACX350A-24	Field cut inner conductor, for sections up to 5 feet
MACX350A-26	Field cut inner conductor, for sections between 5 and 20 feet

MACX450, 4-1/16" 50-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX450-25-*	Variable length inner conductor
MACX450-24	Field cut inner conductor, for sections up to 5 feet
MACX450-26	Field cut inner conductor, for sections between 5 and 20 feet

MACX650, 6-1/8" 50-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX650-25-*	Variable length inner conductor
MACX650-24	Field cut inner conductor, for sections up to 5 feet
MACX650-26	Field cut inner conductor, for sections between 5 and 20 feet

MACX675B, 6-1/8" 75-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX675B-25-*	Variable length inner conductor
MACX675-24	Field cut inner conductor, for sections up to 5 feet
MACX675-26	Field cut inner conductor, for sections between 5 and 20 feet

MACX775, 7-3/16" 75-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX775-25-*	Variable length inner conductor
MACX775-24	Field cut inner conductor, for sections up to 5 feet
MACX775-26	Field cut inner conductor, for sections between 5 and 20 feet

MACX875, 8-1/16" 75-ohm Rigid Line

Supplied with bellows, captivated inner connector, and flange hardware kit.

MACX875B-25-*	Variable length inner conductor
MACX875B-24	Field cut inner conductor, for sections up to 5 feet
MACX875B-26	Field cut inner conductor, for sections between 5 and 20 feet

*Specify flange to flange length of outer conductor in inches (two decimal places)